

Amendments to the Claims:

Please cancel claims 1-7, 15-21, and 29-31 without prejudice. This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (canceled)

2. (canceled)

3. (canceled)

4. (canceled)

5. (canceled)

6. (canceled)

7. (canceled)

8. (previously presented) A method for inserting a portion of a stretch of a pre-wound coil into a slot of a dynamoelectric machine component, the machine component having a bore and a longitudinal axis, the method comprising:

inserting the portion of the stretch into the bore; and

pushing the portion of the stretch into the slot in a direction having a circumferential component with respect to the axis.

9. (previously presented) The method defined by claim 8 wherein the inserting comprises:

pushing the portion of the stretch into the bore; and

guiding the coil with a stationary blade.

10. (previously presented) The method of claim 8 further comprising pressing a portion of the coil into a desired form.

11. (previously presented) The method of claim 10 further comprising compressing the portion of the coil.

12. (previously presented) The method defined by claim 8 further comprising positioning a pushing member in the bore using a moveable blade.

13. (previously presented) The method defined by claim 8 further comprising moveably supporting the coil using a moveable blade during the inserting.

14. (previously presented) The method defined by claim 8 further comprising, when the coil has leads, terminating the leads.

15. (canceled)

16. (canceled)

17. (canceled)

18. (canceled)

19. (canceled)

20. (canceled)

21. (canceled)

22. (previously presented) A method for inserting a portion of a stretch of a pre-wound coil into a slot of a dynamoelectric machine component, the machine component having a bore and a longitudinal axis, the slot

having an opening, the opening facing a direction having a circumferential component with respect to the axis, the method comprising:

inserting the portion of the stretch into the bore; and

pushing the portion of the stretch into the slot.

23. (previously presented) The method defined by claim 22 wherein the inserting comprises:

pushing the portion of the stretch into the bore; and

guiding the coil with a stationary blade.

24. (previously presented) The method of claim 22 further comprising pressing a portion of the coil into a desired form.

25. (previously presented) The method of claim 24 further comprising compressing the portion of the coil.

26. (previously presented) The method defined by claim 22 further comprising positioning a pushing member in the bore using a moveable blade.

27. (previously presented) The method defined by claim 22 further comprising moveably supporting the coil using a moveable blade during the inserting.

28. (previously presented) The method defined by claim 22 further comprising, when the coil has leads, terminating the leads.

29. (canceled)

30. (canceled)

31. (canceled)

32. (previously presented) A method for inserting a coil into a dynamoelectric machine component, the machine component having a bore, a slot, and a longitudinal axis, the method comprising:

placing the coil onto an insertion tool;

inserting a portion of a stretch of the coil into the bore; and

pushing the portion of the stretch into the slot in a direction having a circumferential component with respect to the axis.

33. (previously presented) The method defined by claim 32 further comprising winding the coil outside the machine component.